









Category	Machine Picture	Applicable Products	Picture of Applicable Product	Basic Application	Accuracy	Level of Automation	Labeling Speed	Applicable Product Sizes	Applicable Labels Size	Size of the Machine	Operating Voltage	Note
Folding labeling machine		Power cord labeling, data cable labeling, lollipop labeling, jelly labeling, hardware labeling, etc.		Application of folding labeling, realize the labeling in a variety of tubes, wires and cables, crafts folding labeling, change the jig, can be applied to a variety of different sizes of workpiece labeling.	±0.5mm (excluding product and labeling errors)	Semi-automatic	15-35pcs/min	φ0.9-20mm	W15-80mm L30-400mm	L850*W560*H1100mm	220V50Hz	
Wire Wrap Labeling Machine		Wrap-around attachment of wire and cable labels (barcode labels, warning labels, instruction labels, etc.)		Simply put the wire and cable on the jig, step on the foot pedal machine automatically labeling, labeling machine labeling after the label paper is automatically sent out. Wide range of application, can be applied to a variety of different specifications of the trademark, can meet the length and width of different trademarks of the wrapped coil labeling labeling; high stability by adjusting the range of cylinder stroke to adjust the use of the wire diameter range, easy to operate; the above for the standard model technical parameters, other special requirements and features, can be tailored to customize.	±0.5mm (excluding product and labeling errors)	Semi-automatic	20-23pcs/min	φ4-12mm, φ2-4mm	L18-120 mm (label sizes beyond this size range are acceptable for customization), W6-50 mm	/	220V50Hz	net weight30KG
Semi-automatic Round Bottle Packing Machine		Suitable for various specifications of cylindrical objects labeling, small taper round bottle labeling, such as xylitol, cosmetic round bottles, wine bottles, etc.		It can realize full/half circumference labeling, circumference front and back labeling, and the spacing between front and back labels can be adjusted arbitrarily. Widely used in food, cosmetics, chemical, pharmaceutical and other industries. Optional circumferential positioning detection device to realize circumferential positioning labeling.	±0.5mm (excluding product and labeling errors)	Semi-automatic	20-35pcs/min	φ15-150mm	W10-180mm L15-376mm	L600*W300*H450mm	220V50Hz	
Automatic Round Bottle Packaging Machine (Vertical Round Bottle)		Suitable for pharmaceutical, food, daily chemical and other industries round bottle labeling		It can label full circumference, half circumference, single label, double label, and for the products that need positioning labeling, it can increase the positioning electric eye for product positioning labeling. It can be equipped with automatic turntable bottle trimmer and connected with filling line to improve the production efficiency.	±1mm (excluding product and labeling errors)	Automatic	25-60pcs/min	(For round bottle) φ20-φ120mm	L20-400mm W20-120mm (external dimensions can be customized according to label size)	L1950*W110*H1300mm	220V50Hz60Hz	net weight250KG
Automatic Horizontal Round Bottle Packing Machine		Suitable for labeling the circumference and semi-circumference of cylindrical objects that are not stable enough to stand		Horizontal transmission and horizontal labeling are adopted to increase stability and improve labeling efficiency. Optional coder or printer to the labeling head, which can realize printing production date, batch number and barcode information on the label. Optional coding machine to conveyor belt, can realize printing production date, batch number, bar code and other information on the product before or after labeling.	±0.5mm (excluding product and labeling errors)	Automatic	30-120pcs/min	Outside diameter φ8mm~φ22mm	L20-100mm W20-100mm	L1600*W780*H1400mm	220V50Hz	net weight180KG

Category	Machine Picture	Applicable Products	Picture of Applicable Product	Basic Application	Accuracy	Level of Automation	Labeling Speed	Applicable Product Sizes	Applicable Labels Size	Size of the Machine	Operating Voltage	Note
Automatic Rolling Labeling Machine		Suitable for pharmaceutical, food, daily chemical and other industries round bottle labeling		Full circumference labeling and half circumference labeling are available. It can be equipped with automatic turntable bottle-sorting machine and connected with filling production line to improve the production efficiency. The above is the standard machine technical parameters, other special requirements and functions, can be customized.	±1mm (excluding product and labeling errors)	Automatic	30-80pcs/min	φ25-φ100mm,H15-100mm	W15-100mm L20-380mm	L1900*W1100*H1400mm	220V50Hz60Hz	net weight250KG
Semi-automatic Flat Labeling Machine		Realization of labeling on the plane of various workpieces: such as cosmetic flat bottles, packaging boxes, plastic cap labeling, etc.		Apply suction labeling method, change the labeling mechanism, can be applied to uneven surface labeling, such as concave plane, arc surface labeling. Changing the fixture, it can be applied to labeling of various irregular workpieces.	±0.5mm (excluding product and labeling errors)	Semi-automatic	15-30pcs/min	L20mm-200mm W15mm-110mm; T0.2-120 mm	W15-110mm L15-100mm	L850*W430*H770mm	220V50Hz	
Automatic Plane Labeling Machine		Suitable for sticking labels or self-adhesive film on the upper plane of various items, such as books, folder boxes, cartons, etc.		Replacement of the labeling mechanism can be applied to uneven surface labeling, widely used in large products flat labeling, large scale range of flat objects labeling.	±1mm (excluding product and labeling errors)	Automatic	40-80pcs/min	L40mm-400mm W40mm-200mm; T0.2mm-120mm	W15-120mm L6-190mm	L1600*W780*H1400mm	220V50Hz	
Semi-automatic High Precision Flat Labeling Machine		Realize labeling on the plane of various workpieces, such as chargers, electronic components, plastic cover labeling, etc.		Apply the static pick-up method labeling, realize labeling on the plane of various workpieces, such as chargers, electronic components, plastic cap labeling. High precision, suitable for small labeling products with high precision labeling. Customized automatic high-precision labeling machine is available according to customers' requirements.	±0.3mm (excluding product and labeling errors)	Semi-automatic	15-30pcs/min	L20mm-200mm W20mm-180mm T0.2mm-75mm	W5-70mm L10-700mm	L550*W430*H830mm	220V50Hz	
Automatic Card Labeling Machine		Dedicated to all kinds of card labeling in a variety of plastic sheet surface film protection, high precision, film without bubbles		Dedicated to all kinds of card labeling in a variety of plastic film surface paste protective film, high accuracy, film bubble-free; with automatic product identification function, according to different products automatically enable different labeling head work. Can be used with various packaging lines.	±1mm (excluding product and labeling errors)	Automatic	30-200pcs/min	L40mm-280mm W40mm-200mm T0.2mm-2mm	W20-150mm L6-150mm	L2200*W700*H1400mm	220V50Hz	

Category	Machine Picture	Applicable Products	Picture of Applicable Product	Basic Application	Accuracy	Level of Automation	Labeling Speed	Applicable Product Sizes	Applicable Labels Size	Size of the Machine	Operating Voltage	Note
Automatic Single Side Labeling Machine		Suitable for flat bottles, round bottles, square bottles, such as shampoo flat bottles, laundry detergent, lubricating oil flat bottles, hand sanitizer round bottles, etc. Single-side labeling is widely used in daily chemicals, cosmetics, petrochemicals, pharmaceuticals and other industries, the scope of application is wide		Adopt double side rigid plastic synchronous guiding chain, automatically ensure bottle alignment, low requirements for workers to put bottles and assembly line docking into bottles, greatly reducing the difficulty of workers' work or assembly line docking, can be single machine production, can also be connected to the assembly line production.	±1mm (excluding product and labeling errors)	Automatic	60-120pcs/min	L40mm-400mm W40mm-250mm H50mm-250mm	L6mm-150mm W(Backing paper width)15mm-130mm	L3000*W1500*H1600mm	220V50Hz	net weight500KG
Automatic Double Side Labeling Machine		Suitable for single-side and double-side labeling of flat bottles, round bottles, square bottles, such as shampoo flat bottles, laundry detergent, lubricating oil flat bottles, hand sanitizer round bottles etc.		Double side labeling both sides with double labeling to improve production efficiency, widely used in daily chemical, cosmetic, petrochemical, pharmaceutical and other industries. Wide range of applications, a machine can be compatible with a variety of products (round bottles, flat bottles, square bottles, polygonal bottles, shaped bottles); the use of double-sided rigid plastic synchronous guide chain, automatically ensure bottle alignment, low requirements for workers to put the bottle and the assembly line docking into the bottle, greatly reducing the difficulty of workers or assembly line docking, can be a stand-alone production, can be connected to the assembly line production.	±1mm (excluding product and labeling errors)	Automatic	60-120pcs/min	L40mm-400mm W0mm-250mm H50mm-250mm	L6mm-150mm W(Width of backing paper)15mm-130mm	L3000*W1500*H1600mm	220V50Hz	
Semi-automatic Double-side Labeling Machine		Apply suction labeling method, realize labeling on the side of various workpieces, such as cosmetic flat bottles, packaging boxes, plastic side labeling, etc.		Change the labeling mechanism, can be applied to uneven surface labeling, such as concave plane, arc surface labeling. Change the fixture, which can be applied to labeling of various irregular workpieces. Optional ribbon coder or printer, print the production date and batch number on the label, realize the integration of coding and labeling.  The above is the standard model technical parameters, other special requirements and functions, can be customized.	±0.5mm (excluding product and labeling errors)	Semi-automatic	15-30pcs/min	L20mm-200mm W20mm-150mm H40mm-120mm	L15mm-110mm W(Width of backing paper)15mm-110mm	L1220*W1250*H1470	220V50Hz	net weight270KG
Assembly Line Flat Meter Head Labeling Machine		The assembly line labeling machine is applicable to the assembly line, in a variety of items on the plane of the label or self-adhesive film, such as books, folders, boxes, cartons, etc.		Assembly line labeling machine is suitable for assembly line, in a variety of items on the plane labeling or self-adhesive film, such as books, folders, boxes, cartons, etc., replacement of the labeling mechanism can be applied to uneven surfaces labeling, widely used in large products of the plane labeling, specification range of the plane class objects labeling. According to the application scenario optional purchase of labeling head plate accessories.	±1mm (excluding product and labeling errors)	Automatic	stepper motor:40-150pcs/min; servo motor:50-200pcs/min(Related to product size)	No requirement (depending on assembly line conveying parameters)	L10-250MM, W10-120MM	L1100*W700*H1450mm	220V50Hz	

Category	Machine Picture	Applicable Products	Picture of Applicable Product	Basic Application	Accuracy	Level of Automation	Labeling Speed	Applicable Product Sizes	Applicable Labels Size	Size of the Machine	Operating Voltage	Note
Automatic Assembly Line Side Labeling Head Labeling Machine		Assembly line side labeling		Can be matched to the assembly line, the flow through the product side labeling, to achieve online labeling, such as matching to the spray code conveyor belt, the flow through the items labeling.	±1mm (excluding product and labeling errors)	Automatic	stepper motor:40-150pcs/min; servo motor50-200pcs/min(Related to product size)	No requirement (depending on assembly line conveying parameters)	L10-250MM, W10-120MM	L890*W690*H1430mm	220V50Hz	net weight70KG
Semi-automatic 360° Rotary Labeling Machine		Apply roll-on labeling method, rotate the product through the motor to achieve the labeling of polygonal products such as round bottles, square bottles, hexagonal bottles, tapered bottles etc.		Apply roll-on method labeling, rotate the product by motor to realize the labeling of polygonal products such as round bottle, square bottle, hexagonal bottle, tapered round bottle. Change the fixtures, can be applied to a variety of irregular workpiece labeling. Optional ribbon coder, printing production date and batch number on the label to realize coding-labeling integration.	±1mm (excluding product and labeling errors)	Semi-automatic	15-30pcs/min	L20mm-200mm W20mm-150mm T0.2mm-120mm	W15-380mm L15-110mm	L850*W430*H770mm	220V50Hz	
Semi-automatic Plane Front and Rear Labeling Machine		Plane products, curved products, concave-convex surface products labeling, can also be rotary labeling and front and rear roll labeling combined with the use of labeling, so that it is compatible with more products		Apply the labeling method of labeling and overlaying, applicable to flat products, curved surface products, concave and convex surface products labeling, but also can be rotary labeling and front and rear roll labeling combined with the use of labeling, so that it is more compatible with the product. Can be applied to uneven surface labeling, such as concave plane, arc surface labeling. Change the fixtures, can be applied to a variety of irregular workpiece labeling. Optional ribbon coder, printing production date and batch number on the label to realize coding-labeling integration.	±0.5mm (excluding product and labeling errors)	Semi-automatic	15-30pcs/min	L20mm-200mm W20mm-150mm T0.2mm-120mm	Label Inner Diameterφ76mm Label Outer Diameterφ240mm L15-100mm W15-110mm	L1550*W550*H650mm	220V50Hz	
Automatic Sealing and Corner Labeling Machine		Specialized in box corner labeling, in the box on the plane and the side of the plane corner labeling, to play the role of anti-opening		Dedicated to box corner labeling, in the box on the plane and side plane corner labeling, play the role of anti-detachment. Mainly used in poker, electronic products box tamper-evident labeling. The above is the standard model technical parameters, other special requirements and functions, can be customized.	±1mm (excluding product and labeling errors)	Automatic	30-100pcs/min	L30mm-200mm W30mm-200mm H10mm-60mm	L20-110	L1600*W780*H1400mm	220V50Hz	